



London City Quickview (EGLC/LCY)

N 051°30'19" E 000°03'19" Elev: 149ft

RWY(s)

RWY	Dimensions	Elev	LDA	TORA	ILS
10	1508x30m	16t	1319m	1199m	I-LST 111.15 MHz 095°M 5.5° GP
28	1508x30m	19ft	1319m	1199m	I-LSR 111.15 MHz 275°M 5.5° GP

No tailwind component allowed on approach due steep GP.

ATSU(s)

Position	Frequency
AIR (Tower)	118.075 MHz
INT (Thames Radar)	132.700 MHz
FIN (City Radar)	128.025 MHz
INT and AIR required to open FIN.	

Squawk Codes

Destination	Squawk
local	7030-7077
UK	4301-4377
Ireland	4430-4477
Chan Isl.	7760-7775
Fr/Sp/Po/SAf	2201-2277
Netherlands	7310-7327
US/Can/Carrib	7610-7677
Other	1140-1177

Transition Alt/Level

TA	6000ft
QNH	TL
1032-1050	FL055
1014-1031	FL060
996-1013	FL065
978-995	FL070
960-977	FL075
943-959	FL080

SID(s)

Fix	10	28
BPK	3U	3T
CLN	5U	5T
CPT	4U	4T
DVR	3U	3T
LYD	3U	3T
SAM	4U	4T

Min Stack Level

EGLL QNH	MSL
<978	FL090
978-1013	FL080
>1013	FL070

Stack(s)

Fix	Axis / Dir ⁿ	Min Alt
ALKIN	241° / R	3000ft
SPEAR	195° / R	4000ft

STAR(s)

Fix	Designator
KENET	SPEAR1A
LOGAN	SPEAR1B
DVR	ALKIN3C
SOVAT	ALKIN3D
WAFFU	ALKIN3F
WAL (<FL190)	SPEAR1H
MCT (<FL140)	SPEAR1J
DTY	SPEAR1K
WAL (>FL200)	SPEAR1L
MCT (>FL150)	SPEAR1M

