



Stansted Quickview (EGSS/STN)

N 051°53'06' W 000°14'06' Elev: 348ft

RWY(s)

RWY	Dimensions	Elev	LDA	TORA	ILS	Circ. dir ⁿ
05	3048x45m	332ft	2748m	3048m	I-SED 110.50 MHz 045°M	Right
23	3048x46m	348ft	3048m	3048m	I-SX 110.50 MHz 225°M	

Preferential RWY is 23 when tailwind component is less than 5 knots and the surface is dry.

ATSU(s)

Position	Frequency
GMP (Deliverery)	121.950 MHz
GMC (Ground)	121.725 MHz
AIR (Tower)	123.800 MHz
INT (Essex Radar)	120.625 MHz
FIN (Director)	126.950 MHz
INT and AIR required to open FIN.	

Squawk Codes

Destination	Squawk
local	7030-7077
UK	4301-4377
Ireland	4430-4477
Chan Isl.	7760-7775
Fr/Sp/Po/SAf	2201-2277
Netherlands	7310-7327
US/Can/Carrib	7610-7677
Other	1140-1177

Transition Alt/Level

TA	6000ft
QNH	TL
1032-1050	FL055
1014-1031	FL060
996-1013	FL065
978-995	FL070
960-977	FL075
943-959	FL080

SID(s)

Fix	05	23
BKY	2S	4R
BUZAD	2S	6R
CLN	4S	8R
CPT	2S	3R
DVR	5S	7R
LAM (LL only)	2S	3R
LYD	4S	5R

Min Stack Level

EGLL QNH	MSL
<978	FL090
978-1013	FL080
>1013	FL070

Stack(s)

Fix	Axis / Dir ⁿ	Min Alt
ABBOT	266° / R	MSL + 1
LTN	257° / R	2000ft
LOREL	190° / L	MSL

STAR(s)

Fix	Designator
BKY	ABBOT1A
BARMI	ABBOT1B
IDESI	ABBOT1C
LOGAN	ABBOT1D
DET	ABBOT1E
WCO	LOREL5A
KATHY	LOREL1B
MID	LOREL3C
GIBSO	LOREL1D
WAL (>FL200)	LOREL4F
MCT (>FL150)	LOREL3G
WAL (<FL190)	LOREL1H
MCT (<FL140)	LOREL1J
DTY	LOREL1K
KENET (>FL90)	LOREL2L
KENET (<FL80)	LOREL2M
HAZEL	LOREL2N
SAM	LOREL2P
GURLU	LOREL2Q
ABBOT	LOREL1R
BEDEK	LOREL2S



Great Britain

Stansted Quickview (EGSS/STN)

